



- 1. EXTRUDED ALUM FILLER 10 "
- 3. EXTRUDED ALUM FLAT RETAINER 1.5 "
- 4. SHEET ALUM .063 "
- 5. ANGLE STEEL 1.5" X 1.5" X .1875"
- 6. TUBE STEEL RECT 2" X 4" X .250" WITH HOLES
- 7. TUBE STEEL RECT 2" X 4" X .250"
- 8. TUBE STEEL SQ 4" X 4" X 11 GA.
- 9. PLATE STEEL 5/8 " X 6 " X 12 "
- 10. ANGLE ALUM 1.5" X 1.5" X .125"
- 11. ANGLE ALUM 2" X 2" X .187"
- 12. HAT SECTION 24 GA. GALVANIZED
- 13. LAMP FLUORESCENT 96 " (4)
- 14. BALLAST 2040-24 ADVANCE (1)
- 15. 5/16" X 1 1/2" SELF-TAPPING BOLTS (4)
- 16. 3/4" X 30" ANCHOR BOLTS (4)
- 17. 3000 PSI CONCRETE (MINIMUM)
- 18. #4 REBAR GRADE 60 OR BETTER

SAMPLE FOUNDATION DRAWING

SCALE:
1/2" = 12"

NOTE: INTERNAL BRACING, LAMP SIZE AND LOCATIONS SHOWN ON THIS DRAWING ARE FOR CONCEPTUAL REFERENCE ONLY. THERE MAY BE SOME DEVIATIONS AS NECESSARY ON THE FINISHED PRODUCT TO ENSURE EVEN LIGHTING.